



Hazardous Location Alternators

ATEX / IECEx d IIB: Flameproof

C192: 14 volt 70 amp - SIRA certified
C193: 28 volt 35 amp - SIRA certified

- 4 inch hinge mount
- Cable, gland and fan pulley included
- Internally rectified and regulated
- Meets IEC 60079-0 and 60079-1

United States Coast Guard
Compliant for Class 1, Zone
1 Group IIB Locations



Class 1 Division 1: Explosion proof

C184: 14 volt 50 amp - Group C, D T5 - CSA certified
C186: 28 volt 50 amp - Group C, D T5 - CSA certified

- SAE 2 inch spool mount
- Remotely rectified and regulated
- Interconnect cable available



Class 1 Division 2: Non-incendive

C130: 24 volt 60 amp - Group D T3 - UL / CSA certified
C131: 14 volt 70 amp - Group B, C, D T3C - CSA certified
C132: 28 volt 60 amp - Group B, C, D T3C - CSA certified

- SAE 2 inch spool mount
- Self or ignition excite



Increased safety - Totally enclosed

C172: 14 volt 70 amp
C173: 28 volt 35 amp

- SAE 4 inch spool mount
- Ideal for off-shore and high debris applications



For inquiries call 847-866-6030
contact sales@ceniehoff.com
visit us at www.CENiehoff.com
2021 Lee St. Evanston IL, 60202 USA